

KemTab

Art. No.: 99 851



Applications

- For plasma cutting up to 300 amps
- For flame cutting with steel plates up to 150 mm

Benefits

- No external follow-up costs caused by in-house production of wear parts due to easyFRAME
- No cleaning or maintenance required on the material support as it can be easily replaced (easyFRAME)
- Time and cost savings when cleaning the table due to large slag trays and thus longer cleaning intervals
- Energy cost savings due to low extraction volume thanks to individual control of the extraction dampers of the section in use.
- Integrated spark elimination for more safety

Technical Data

Art. No.	99 851
Basic data	
Table width (Material support)	1.600 mm, 2.100 mm, 2.600 mm, 3.100 mm
Table height	700 mm
Segment distance	515 mm, 690 mm, 1.030 mm

Properties

- Thanks to the modular design, any table size can be created
- The new modular system, which enables the right equipment for all applications. This offers configuration options from a low-cost entry (for lower requirements) up to a fully equipped table (for high requirements)
- Innovative new flap system optimized for air technology
- Various control options of the extraction damper in the individual table segments (Mechanical / Mechanical – Pneumatic / E – Pneumatic)
- Adjustable control slide that can be adapted to the different conditions (only with mechanical or mechanical – pneumatic flap control)
- Flow-optimized air guidance for low losses
- Particularly large extraction channel for low resistance
- Welded or interlocking material support (easyFrame)
- Low service requirements due to separation of air flow and external conditions